

Powerbase 70-BMCC Instruction Manual

1. Using contact block GP-DV-BMCC the Powerbase 70 can supply 12V for the Black Magic Cinema Camera with a the proprietary pin connection. It can also supply 12V for accessories through the contact block's powertap socket.



- 2. Included GP-DV-BMCC to power camera models:
- -Black Magic Cinema Camera

Specifications

Rated Voltage: 14.8V Rated Capacity: 77Wh Charge Time: 3~5 hrs

Dimensions: 6.25in x 3.4in x 2in


Weight: 1.5lbs

Four step LED power indication


Remaining Capacity (%)	LED1	LED2	LED3	LED4
0%	OFF	OFF	OFF	OFF
<10%	FLASH	OFF	OFF	OFF
10%-25%	ON	OFF	OFF	OFF
25%-50%	ON	ON	OFF	OFF
50%-75%	ON	ON	ON	OFF
≥75%	ON	ON	ON	ON




- 1. Can be used as normal V type brick battery
- 2. Built-in PT port can supply power for accessories or charging.




3. Quick release plate can be used to install wireless reciever, hard drive or other equiptment or to connect two batteries.



4. Both sides have a 1/4" 20 insert for installing other equipment





WARNING:

IF USING THE PB-70C CHARGER FOR CHARGING, PLUG THE CHARGER DIRECTLY INTO THE BATTERY. NEVER CHARGE THROUGH THE POWERBASE INTERCHANGEABLE REGULATOR BLOCKS!

Switronix, Inc. 87 Garden St Westbury, NY 11590

Tel: 1-800-613-7948, 516-750-9675 Fax: 516-594-1414 Website: http://www.switronix.com