



CPS1215RMS Rackbar™ Surge Protectors



Designed for data centers and other electrically demanding applications.

Engineered for the most demanding applications, the professional-grade Rackbar™ CPS1215RMS safeguards systems and networking equipment by absorbing spikes in energy caused by storms and electrical power surges. Designed for network environments, the CPS1215RMS also performs superbly for home office use, providing 1800 joules of protection, 15-Amp electrical capacity with circuit breaker, and 12 surge-protected outlets (6 front, 6 rear). Industrial-grade metal housing keeps this Rackbar performing flawlessly. The CPS1215RMS has a 1U racksize and can be mounted vertically or horizontally.

Features of the CPS1215RMS include an EMI/RFI noise filter, industrial-grade metal housing, AC power cord (15 ft.). The CPS1215RMS also comes with a three-year limited warranty.

TYPICAL APPLICATIONS

- Data Centers
- Network Closets
- VoIP Phone Systems

FEATURES

- Twelve (12) outlets
- Three-year limited warranty

SPECIFICATIONS

GENERAL		PHYSICAL	
Type	Surge Protector	Rack Size	1U
INPUT		Dimensions - W×H×D (in)	17.25 × 1.75 × 4.75 inches
Voltage	120 V	Weight (lbs)	5.0 lbs
Plug Type	NEMA 5-15P	ENVIRONMENTAL	
Plug Style	Straight	Operating Temperature	32 - 95 °F (0 - 35 °C)
Cord Length	15 ft	Operating Humidity	0 - 95% (non-condensing)
Switch	Lighted On/Off	Storage Temperature	5 - 113 °F (-15 - 45 °C)
OUTPUT		Maximum Operating Elevation	10,000 ft (3,000 m)
Outlet Type	NEMA 5-15R	Maximum Storage Elevation	50,000 ft (15,000 m)
Outlets - Front	6	CERTIFICATIONS	
Outlets - Rear	6	Safety	UL Recognized
Outlets - Total	12	Environmental	RoHS Compliant
SURGE PROTECTION & FILTERING		WARRANTY	
Surge Suppression	1,800 joules	Product Warranty	Limited Lifetime
Clamping Voltage	400V (N-H, N-G), 500V (L-G)	Connected Equipment Guarantee	None
EMI/RFI Filtration	150 KHz - 150 MHz		