



## 50mm T1.5 CINE DSX Instruction Manual

Thank you for purchasing the ROKINON Cine DSX 50mm T1.5 Full Frame prime lens.

Please read this instruction manual prior to use to familiarize yourself with functions of the lens, the operating method, and cautions.

## FEATURES


- Available in mounts to fit all major camera brands, and offering Full Frame coverage, it will provide high quality video and still images with Mirrorless and DSLR cameras of any sensor size.
- •The fast T1.5 aperture supports shooting even in low-light situations, and can provide a shallow depth of field for precise selective focus control to highlight your subject.

- It offers full cine lens features including a de-clicked aperture control, industry standard 0.8 MOD focus and aperture ring gearing, a precise and smooth long focus throw, T-stop calibration, and tight color matching.
- Additional features include a nine blade aperture for smoother bokeh, weather sealed mounts (Except Nikon), and the distance scales, aperture settings, and focal length markings are visible from both sides of the lens.
- The nine elements in six groups design utilizes two specialized elements including one Aspherical and one Hybrid Aspherical types, plus UMC anti-reflective coatings for clear and vibrant images.
- Its compact size and light weight design with gears that are designed to be smoother to the touch, enhance comfort and stability for hand-held and gimbal shooting.

#### Cautions

- Do not look directly at the sun through the lens as it may seriously impair your vision.
- Attach or detach the lens only while the camera is turned off.
- Protect the lens from water, high humidity and excessive heat.
- Avoid subjecting the lens to drastic temperature changes such as moving from a very cold outdoors location to a warm indoors location. This can cause moisture in the air to condense inside or on the outside of the lens and lead to failure or mold production.
- Before taking the lens indoors from a cold outdoors location, put the lens in a plastic bag or sealed camera bag, and remove it only when the lens has warmed up to room temperature.

#### Parts



### Attaching the Lens

Align the index mark on the lens barrel with the index mark on the lens mount of the camera.

 Do not press the lens release button on the camera when mounting the lens.

-Insert the lens into the camera mount and rotate it clockwise
(Counterclockwise for Nikon mounts) until it "clicks" and locks into
place. Do not insert the lens at an angle.

Remove the front lens cap when you are ready to shoot.

Attach the front lens can

While holding down the lens release button on the camera body, rotate the lens counterclockwise (Clockwise for Nikon mounts) until it stops and separate the lens from the body.

Attach the rear lens cap.

## Aperture Adjustment and Exposure Modes

If your camera will not record video or shoot in still mode, make sure you are in either Manual or Aperture Priority exposure control mode, and that "release without lens" is enabled within your camera's menus.

 Aperture adjustment is done directly on the aperture ring of the lens, NOT from a control on your camera.

• It is suggested that ISO be set manually, NOT on auto. Set it to a sensitivity appropriate for the subject, lighting conditions, and speed/aperture settings you want to utilize

#### Focusina

Check your camera's instruction book for manual focusing methods including Focus Peaking and Focus Magnification. Please note that available focusing methods may vary depending on your camera model.

- Set the Focus Mode of your camera to Manual Focus.
- Set the lens to its maximum aperture of T1.5. This enables you to critically focus by eliminating the influence that depth of field provides at smaller apertures.
- After achieving critical focus at T1.5, set your shooting aperture.
- Precise Infinity Focus NOT located at the focus stop at the infinity end
  of the focus scale. The exact point on the focusing scale for critical
  infinity focus will vary depending on camera and lens mount, wear,
  temperature, and normal design tolerances.

## Cleaning

- It is extremely important before cleaning to dust off the lens surface using a lens blower or a soft brush to remove any foreign particles or grit that could scratch the lens.
- For stubborn spots, use only one or two small drops of a reputable lens cleaner on a microfiber cloth, and gently wipe the lens in a circular motion.

DO NOT USE AN ORGANIC SOLVENT SUCH AS PAINT THINNER, ALCOHOL, OR BENZENE.

Model	ROKINON CINE DSX 50mm T1.5						
Aperture Range	T1.5 ~ 22						
Mount	CANON EF	CANON RF	NIKON	SONY E	FUJI X	CANON M	MFT
Angle of View (Full Frame / APS-C)	46.2°/ 29.4°	46.2° / 29.4°	46.2°/ 31.3°	46.2°/ 31.3°	31.3°	29.4°	23.6°
Length	2.94° (74.7mm)	3.89* (98.7mm)	2.84" (72.2mm)	3.96" (100.7mm)	3.98° (101mm)	3.96" (100.6mm)	3.92° (99.5mm)
Weight	18.57az (525.8g)	20.83oz (990.6g)	18.16oz (514.8g)	20.33oz (576.4g)	20.01oa (567.4g)	20.08oz (569.4g)	19.89oz (563.8g)
Optical Construction	9 Elements in 6 Groups (1 ASP, 1 Hybrid ASP, with UMC Coating)						
Minimum Focusing Distance	17.7"(0.45m)						
Filter Size	77mm						
Number of Aperture Blades	9						
Maximum Diameter	3.31*(84mm)						
Focus Throw/ Aperture Throw	150° / 48°						

- The minimum focus is the distance from the image sensor to the object.
- The product specifications and exterior are subject to change without notice.
- The supported functions of this product may vary according to the camera brand and model.

#### Included Components Instruction Manual/ Warranty • Front Lens Cap • Soft Lens Pouch • Rear Lens Cap

## Contacts

Elite Brands Inc. ROKINON Division New York, NY 10005 Toll Free: 800.441.1100 Phone: 212.947.7100 support@rokinon.com

rokinon.com facebook.com/rokinonlenses instagram.com/rokinon

ROKINON\* is a registered trademark of Elite Brands Inc. ©2020, Elite Brands Inc., New York, NY 10005



# INFORTANT! Before sendrottur roddion Leik of accessory please Call 1-801-441-1101/(212) 917-1100 Por Technolal Support to Ostan a markanty altycordation #

The product on the right is determined to be deficiled a Ammatty authorization number will be provided.
 Please includes a copy of this document with all intervention flect in and dated proof of purchase.
 Pagin the equipment accessed purchase consultantly amended and their play proposition intervention to the proof or intervention to the proof of the proof or intervention to the proof or intervention to the proof of the proof or intervention to the proof of the pro

#### RONINGN U.S.A. LINITED TWO YEAR WARRANTY

You PCK NOA populat of the model and serial number on the right is warranted by Ellis Blands Inc. against delective workmanship or materials for two full years from the date of purchase.

The Branch is v. W will be option, either repair or regions equipment which is returned preguid and incured to fine address above. The product must be accompanied by the region of set also showing proof of date of purchase and a copy of the Certificate of Quility with all of the required information. Brain is considered to the contraction of the production is continued to the accompanied to His is because the grant to be diseased in the classification of the contract of the contract

	Translating year you spoots ago group any put was been been then there is who it wan in thom since to be after account industries.  CONCEPTING THE ADOCTOR CELLED BROOKS INC., ATTRE WIRPHARTY SEPTIACE 40 likel Brook, 16 or Floor, New York, NY 1000 LISA.  Brook support Brokeron con Phone (2) 2) 917 7100					
١	Date of Date of					



Certificate of Quality Thank you or Purchasing a Rokinon product. Rokinon lenses and accessories

