



DL (Dry Lock) Port System Charts for Sony Alpha Series Cameras

PORT OPTIONS

Some lenses have more than one port option. The first column is always the recommended option for the best compromise of imaging quality, performance, and handling with any given lens.

PRODUCT(S) REQUIRED

Where multiple lines of products are listed for a given option, all products listed are required to make a complete compatible lens port.

LENSES REFERENCING “+4 DIOPTER REQUIRED”

[Why Your Lens May Need a +4 Diopter Underwater](#)

A +4 diopter is available for purchase through your local camera store, and is commonly sold in a set with +1 and +2 close-up lenses. Common brands include Tiffen and Hoya. Make sure to purchase the correct size for your lens. The thread diameter is usually referenced on the front of the lens in millimeters (ø 58mm, 67mm, etc.). All photos will be out of focus if a +4 diopter is required but not used.

HELPFUL LINKS

[When to Use a Compact 8" Dome Port Underwater](#)

[How to Polish an Acrylic Dome Port](#)

[Dealing with Droplets when Shooting Split Shots](#)

[Why You Need a Fisheye Lens Underwater](#)

[The Right Lens for Every Situation Underwater](#)

[5 Situations Where You Need a Strobe Underwater](#)

Sony E-Mount Lenses

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
8 mm Rokinon Fisheye	Not recommended due to extreme vignetting.		
8-15 mm Canon EF f/4L Fisheye USM + Metabones Canon EF Lens to Sony E Mount T Smart Adapter (Mark IV) or Sigma MC-11 Adapter “BEST LENS” <i>Tripod foot must be removed from adapter.</i>	Lens shade must be removed. Dome shade must be removed to eliminate vignetting. AF only. <u>Product(s) required:</u> 75340 Dome Port 75020 Extension 5509.28 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight	Lens shade must be removed. Dome shade must be removed to eliminate vignetting. AF only. <u>Product(s) required:</u> 75348 Dome Port 75028 Extension 5509.28 Zoom Gear	
10 mm Venus Optics Laowa f/2.8 Zero-D FF See Installation See First Impressions See Results	Dome shade must be removed to eliminate vignetting. AF only. <u>Product(s) required:</u> 75340 Dome Port 75020 Extension <u>Optional accessories:</u> 47140 Trim Weight		
10-18 mm Sony E f/4 OSS	AF only. <u>Product(s) required:</u> 75340 Dome 5509.28 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight		
10-18 mm Sigma f/2.8 DC DN Contemporary	Compact and lightweight for travel. Better for close focus wide angle. AF only. <u>Product(s) required:</u> 75344 Compact Dome Port 5509.29 Zoom Gear	Larger dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 75340 Dome Port 5509.29 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
10-20 mm Sony E f/4 PZ G See Results	Compact and lightweight for travel. Better for close focus wide angle. AF only. <u>Product(s) required:</u> 75344 Compact Dome Port <u>Optional accessories:</u> 5509.51 Zoom Gear** ** Zoom without optional zoom gear by custom assigning zoom function to the directional pad buttons.	Larger dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 75340 Dome Port <u>Optional accessories:</u> 47140 Trim Weight 5509.51 Zoom Gear** ** Zoom without optional zoom gear by custom assigning zoom function to the directional pad buttons.	
11 mm Sony E f/1.8	Compact and lightweight for travel. Better for close focus wide angle. AF only. <u>Product(s) required:</u> 75344 Compact Dome Port	Larger dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 75340 Dome Port <u>Optional accessories:</u> 47140 Trim Weight	
11-18 mm Tokina f/2.8	Compact and lightweight for travel. Better for close focus wide angle. AF only. <u>Product(s) required:</u> 75348 Dome Port 5509.28 Zoom Gear	Larger dome is best for split shots (half-in, half-out of the water). May have slightly better edge sharpness compared to compact dome. AF only. <u>Product(s) required:</u> 75340 Dome Port 5509.28 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
11-20 mm Tamron f/2.8 Di III-A RXD	Compact and lightweight for travel. Better for close focus wide angle. May use alternative extension as short as 37mm with some negative effect on edge sharpness. Use thinnest foam strips with zoom clamp. AF only. Product(s) required: 75344 Compact Dome Port 75050 Extension 5509.29 Zoom Gear	Larger dome is best for split shots (half-in, half-out of the water). May have slightly better edge sharpness compared to compact dome. May use alternative extension as short as 28mm with some negative effect on edge sharpness. Use thinnest foam strips with zoom clamp. AF only. Product(s) required: 75340 Dome Port 75042 Extension 5509.29 Zoom Gear Optional accessories: 47140 Trim Weight	
12 mm Carl Zeiss Touit 2.8/12	Dome shade must be removed to eliminate vignetting. AF only. Product(s) required: 75340 Dome Port 75020 Extension 0923.81 Anti-Reflection Ring		
12 mm Rokinon f/2.8 Full Frame Fisheye + Metabones Canon EF Lens to Sony E Mount T Smart Adapter (Mark IV) or Sigma MC-11 Adapter <i>Tripod foot must be removed from Metabones adapter.</i>	Port recommendation not available.		
12-24 mm Sony f/2.8 FE GM	AF only. Product(s) required: 75340 Dome Port 75037 Extension 5509.41 Zoom Gear Optional accessories: 47140 Trim Weight	Compact 8" dome port is not recommended due to vignetting.	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
12-24 mm Sony f/4 FE G See Installation	Compared to shorter ports, this option puts the lens element closest to the center of the dome sphere for optimal sharpness. Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75050 Extension 5509.32 Zoom Gear Optional accessories: 47140 Trim Weight	AF only. Product(s) required: 75340 Dome Port 75020 Extension 5509.32 Zoom Gear Optional accessories: 47140 Trim Weight	
14 mm Sony f/1.8 GM	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75020 Extension Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port 75037 Extension	
14 mm Samyang f/2.8 AF FE Art	AF only. Product(s) required: 75340 Dome Port 75020 Extension Optional accessories: 47140 Trim Weight		
14 mm Sigma f/1.8 DG HSM Art	AF only. Product(s) required: 75340 Dome Port 75050 Extension Optional accessories: 47140 Trim Weight		

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
14-24 mm Sigma f/2.8 DG DN Art	AF only. <u>Product(s) required:</u> 75340 Dome Port 75020 Extension 75042 Extension 5509.49 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight		
15 mm Sony E f/1.4 G	Compact and lightweight for travel. Better for close focus wide angle. AF only. <u>Product(s) required:</u> 75344 Compact Dome Port	Larger dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 75340 Dome Port <u>Optional accessories:</u> 47140 Trim Weight	
15 mm Sigma f/1.4 Fisheye DG DN Art	Port recommendation not available. This lens may not be able to be used behind a dome port underwater due to its long minimum focus distance (15.2").		
15 mm Sigma f/2.8 EX DG Diagonal Fisheye + Metabones Canon EF Lens to Sony E Mount T Smart Adapter (Mark IV) or Sigma MC-11 Adapter <i>Tripod foot must be removed from adapter.</i>	AF only. <u>Product(s) required:</u> 75340 Dome Port <u>Optional accessories:</u> 47140 Trim Weight		
16 mm Sigma f/1.4 DC DN	Compared to shorter ports, this option puts the lens element closest to the center of the dome sphere for optimal sharpness. AF only. <u>Product(s) required:</u> 75340 Dome Port 75042 Extension <u>Optional accessories:</u> 47140 Trim Weight	AF only. <u>Product(s) required:</u> 75340 Dome Port 75028 Extension <u>Optional accessories:</u> 47140 Trim Weight	AF only. <u>Product(s) required:</u> 75340 Dome Port <u>Optional accessories:</u> 47140 Trim Weight

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
16 mm Sony FE f/1.8 G	Compared to shorter ports, this option puts the lens element closest to the center of the dome sphere for optimal sharpness. Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75042 Extension Optional accessories: 47140 Trim Weight	AF only. Product(s) required: 75344 Compact Dome Port 75037 Extension	AF only. Product(s) required: 75340 Dome Port Optional accessories: 47140 Trim Weight
16 mm Sony E f/2.8 Pancake	Vignetting (dark shadows in the corners of the image) will be present. AF only. Product(s) required: 75340 Dome Optional accessories: 47140 Trim Weight		
16 mm Sony E f/2.8 Pancake + Fisheye Converter VLC-ECF1	AF only. Product(s) required: 75340 Dome Optional accessories: 47140 Trim Weight		
16 mm Sony E f/2.8 Pancake + Ultra Wide Converter VLC-ECU1	AF only. Product(s) required: 75340 Dome Optional accessories: 47140 Trim Weight		

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
16-25 mm Sony FE f/2.8 G See Installation	Compared to shorter ports, this option puts the lens element closest to the center of the dome sphere for optimal sharpness. Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required 75340 Dome Port 75050 Extension 5509.28 Zoom Gear 0923.78 Anti-Reflection Ring Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. AF only. Product(s) required 75344 Compact Dome Port 75020 Extension 75037 Extension 5509.28 Zoom Gear 0923.78 Anti-Reflection Ring	Edges will be softer compared to longer port options. AF Only. Product(s) required 75340 Dome Port 5509.28 Zoom Gear 0923.78 Anti-Reflection Ring Optional accessories: 47140 Trim Weight
16-28 mm Sigma f/2.8 DG DN	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75028 Extension 5509.28 Zoom Gear Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port 75028 Extension 5509.28 Zoom Gear	
16-30 mm Tamron f/2.8 Di III VXD G2	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75050 Extension 5509.28 Zoom Gear Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Can alternatively use Extended Compact Dome Port # 75348. Product(s) required: 75344 Compact Dome Port 75050 Extension 5509.28 Zoom Gear	Edges will be softer compared to longer port options. AF Only. Product(s) required 75340 Dome Port 5509.28 Zoom Gear Optional accessories: 47140 Trim Weight

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
16-35 mm Sony FE f/2.8 GM (Mark I) See Installation	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75028 Extension 75050 Extension 5509.16 Zoom Gear 0923.74 Anti-Reflection Ring Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port 75028 Extension 75050 Extension 5509.16 Zoom Gear 0923.74 Anti-Reflection Ring	
16-35 mm Sony FE f/2.8 GM II	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75020 Extension 75050 Extension 5509.38 Zoom Gear 0923.74 Anti-Reflection Ring Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port 75020 Extension 75050 Extension 5509.38 Zoom Gear 0923.74 Anti-Reflection Ring	Shortest combination physically possible. We recommend a longer combination for better edge sharpness. AF only. Product(s) required: 75340 Dome Port 75028 Extension 75037 Extension 5509.38 Zoom Gear 0923.74 Anti-Reflection Ring Optional accessories: 47140 Trim Weight
16-35 mm Sony FE f/4 G PZ “BEST LENS” See Review See More Photos	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75042 Extension 0923.76 Anti-Reflection Ring Optional accessories: 47140 Trim Weight 5509.16 Zoom Gear** ** Zoom without optional zoom gear by custom assigning zoom function to the directional pad buttons.	Not recommended for photos where edge sharpness is important. Compact and lightweight for travel. AF only. Product(s) required: 75344 Compact Dome Port 75042 Extension 0923.76 Anti-Reflection Ring Optional accessories: 5509.16 Zoom Gear** ** Zoom without optional zoom gear by custom assigning zoom function to the directional pad buttons.	We recommend a longer combination (Option 1) for better edge sharpness. AF only. Product(s) required: 75340 Dome Port 75020 Extension 0923.76 Anti-Reflection Ring Optional accessories: 47140 Trim Weight 5509.16 Zoom Gear** ** Zoom without optional zoom gear by custom assigning zoom function to the directional pad buttons.

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
16-35 mm Sony FE f/4 ZA OSS Vario Tessar T* See Installation	Superior edge sharpness compared to shorter ports. Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75042 Extension 5509.48 Zoom Gear 0923.72 Anti-Reflection Ring Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port 75042 Extension 5509.48 Zoom Gear 0923.72 Anti-Reflection Ring	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 5509.48 Zoom Gear 0923.72 Anti-Reflection Ring Optional accessories: 47140 Trim Weight
16-35 mm Canon EF f/2.8L II USM + Metabones Canon EF Lens to Sony E Mount T Smart Adapter (Mark IV) or Sigma MC-11 Adapter <i>Tripod foot must be removed from Metabones adapter.</i>	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75042 Extension 75050 Extension 5509.28 Zoom Gear 0923.04 Anti-Reflection Ring Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port 75042 Extension 75050 Extension 5509.28 Zoom Gear 0923.04 Anti-Reflection Ring	
16-35 mm Canon EF f/2.8L III USM + Metabones Canon EF Lens to Sony E Mount T Smart Adapter (Mark IV) or Sigma MC-11 Adapter <i>Tripod foot must be removed from Metabones adapter.</i>	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port (2) 75050 Extensions 5509.12 Zoom Gear 0923.05 Anti-Reflection Ring Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port (2) 75050 Extensions 5509.12 Zoom Gear 0923.05 Anti-Reflection Ring	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
16-35 mm Canon EF f/4L USM + Metabones Canon EF Lens to Sony E Mount T Smart Adapter (Mark IV) <i>Tripod foot must be removed from Metabones adapter.</i>	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75042 Extension 75050 Extension 5509.28 Zoom Gear 0923.01 Anti-Reflection Ring Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port 75042 Extension 75050 Extension 5509.28 Zoom Gear 0923.01 Anti-Reflection Ring	
16-50 mm Sony E f/3.5-5.6 PZ OSS	Larger dome is best for split shots (half-in, half-out of the water). Zoom by custom assigning zoom function to the directional pad buttons. AF only. Product(s) required: 75340 Dome Port 75037 Extension 0923.73 Anti-Reflection Ring Optional accessories: 47140 Trim Weight	Not recommended for photos where edge sharpness is important. Compact and lightweight for travel. Zoom by custom assigning zoom function to the directional pad buttons. AF only. Product(s) required: 75344 Compact Dome Port 75037 Extension 0923.73 Anti-Reflection Ring	We recommend a longer combination (Option 1) for better edge sharpness. Zoom by custom assigning zoom function to the directional pad buttons. AF only. Product(s) required: 75340 Dome Port 0923.73 Anti-Reflection Ring Optional accessories: 47140 Trim Weight
16-55 mm Sony E f/2.8 G	Larger dome is best for split shots (half-in, half-out of the water). Use zoom clamp without foam strips. AF only. Product(s) required: 75340 Dome Port 75050 Extension 5509.27 Zoom Gear Optional accessories: 47140 Trim Weight	We recommend a longer combination (Option 1) for better edge sharpness. AF only. Product(s) required: 75340 Dome Port 75028 Extension 5509.27 Zoom Gear Optional accessories: 47140 Trim Weight	Compact dome port not recommended due to severe vignetting.

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
16-70 mm Sony E f/4 ZA OSS Vario-Tessar T* 	May give very slightly better edge sharpness compared to other port options. Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: +4 Diopter Required 75340 Dome Port 75020 Extension 75028 Extension 5509.27 Zoom Gear Optional accessories: 47140 Trim Weight	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: +4 Diopter Required 75340 Dome Port 75042 Extension 5509.27 Zoom Gear Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: +4 Diopter Required 75344 Compact Dome Port 75020 Extension 75028 Extension 5509.27 Zoom Gear
17-28 mm Tamron f/2.8 Di III RXD E-Mount 	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75050 Extension 5509.29 Zoom Gear Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port 75028 Extension 75037 Extension 5509.29 Zoom Gear	
17-40 mm Canon f/4.0L EF USM + Metabones Canon EF Lens to Sony E Mount T Smart Adapter (Mark IV) <i>Tripod foot must be removed from adapter.</i>	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75020 Extension 75050 Extension 5509.28 Zoom Gear 0923.02 Anti-Reflection Ring Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port 75020 Extension 75050 Extension 5509.28 Zoom Gear 0923.02 Anti-Reflection Ring	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
17-50 mm Tamron f/4 Di III VXD	Larger dome is best for split shots (half-in, half-out of the water). Compared to shorter ports, this option puts the lens element closest to the center of the dome sphere for optimal sharpness. AF Only. Product(s) required 75340 Dome Port 75028 Extension 75037 Extension 5509.28 Zoom Gear	Larger dome is best for split shots (half-in, half-out of the water). AF Only. Product(s) required 75340 Dome Port 75020 Extension 75042 Extension 5509.28 Zoom Gear	Compact and lightweight for travel. AF Only. Product(s) required 75344 Compact Dome Port 75020 Extension 75050 Extension 5509.28 Zoom Gear
18 mm Zeiss Batis f/2.8	Larger dome is best for split shots (half-in, half-out of the water). Compared to shorter ports, this option puts the lens element closest to the center of the dome sphere for optimal sharpness. AF only. Product(s) required: 75340 Dome Port 75028 Extension 0923.82 Anti-Reflection Ring Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port 75028 Extension 0923.82 Anti-Reflection Ring	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 0923.82 Anti-Reflection Ring Optional accessories: 47140 Trim Weight

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
18-105 mm Sony E PZ f/4 G OSS	Larger dome is best for split shots (half-in, half-out of the water). Compared to shorter ports, this option puts the lens element closest to the center of the dome sphere for optimal sharpness. Diopter required for focusing behind a dome underwater, but prevents focusing at infinity above the surface. AF only. Product(s) required: +4 Diopter Required 75340 Dome Port** 75050 Extension 75028 Extension Optional accessories: 47140 Trim Weight ** Zoom by custom assigning zoom function to the directional pad buttons.	Compact and lightweight for travel. Better for close focus wide angle. Diopter required for focusing behind a dome underwater, but prevents focusing at infinity above the surface. AF only. Product(s) required: +4 Diopter Required 75344 Compact Dome Port** 75050 Extension 75028 Extension Optional accessories: 47140 Trim Weight ** Zoom by custom assigning zoom function to the directional pad buttons.	Larger dome is best for split shots (half-in, half-out of the water). Diopter required for focusing behind a dome underwater, but prevents focusing at infinity above the surface. AF only. Product(s) required: +4 Diopter Required 75340 Dome Port** 75050 Extension Optional accessories: 47140 Trim Weight ** Zoom by custom assigning zoom function to the directional pad buttons.
18-200 mm Sony E f/3.5-6.3 OSS 18-200 mm Sony E f/3.5-6.3 OSS LE	Port recommendation not available.		
20 mm Sony FE f/1.8 G	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port 75028 Extension	Larger dome is best for split shots (half-in, half-out of the water). Compared to shorter ports, this option puts the lens element closest to the center of the dome sphere for optimal sharpness. AF only. Product(s) required: 75340 Dome Port 75020 Extension Optional accessories: 47140 Trim Weight	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port Optional accessories: 47140 Trim Weight

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
20 mm Sony E f/2.8	AF only. <u>Product(s) required:</u> 75340 Dome Port <u>Optional accessories:</u> 47140 Trim Weight		
20-40 mm Tamron f/2.8 Di III VXD	AF only. <u>Product(s) required:</u> 75340 Dome Port 5509.28 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight		
20-70 mm Sony FE f/4 G	Larger dome is best for split shots (half-in, half-out of the water). Compared to shorter ports, this option puts the lens element closest to the center of the dome sphere for optimal sharpness. AF only. <u>Product(s) required:</u> 75340 Dome Port 75050 Extension 5509.55 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. <u>Product(s) required:</u> 75344 Compact Dome Port 75020 Extension 75050 Extension 5509.55 Zoom Gear	Larger dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 75340 Dome Port 75042 Extension 5509.55 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight
24 mm Sony FE f/1.4 GM	Larger dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 75340 Dome Port 75028 Extension <u>Optional accessories:</u> 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. <u>Product(s) required:</u> 75348 Dome Port 75028 Extension	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
24 mm Samyang f/2.8 AF FE	AF or MF. Manual focus requires optional focus gear. Product(s) required: 75340 Dome Port Optional accessories: 5509.27 Focus Gear		
24 mm Sigma f/1.4 DG HSM Art + Metabones Canon EF Lens to Sony E Mount T Smart Adapter (Mark IV) <i>Tripod foot must be removed from adapter.</i>	AF only. Product(s) required: 75340 Dome Port 75028 Extension Optional accessories: 47140 Trim Weight		
24 mm Tamron f/2.8 Di III OSD	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port	
24-50 mm Sony f/2.8 G	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75020 Extension 5509.28 Zoom Gear	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port 75028 Extension 5509.28 Zoom Gear	
24-70 mm Sigma f/2.8 DG DN Art <u>"BEST LENS"</u> See Installation	Compared to shorter ports, this option puts the lens element closest to the center of the dome sphere for optimal sharpness. AF only. Product(s) required: 75340 Dome Port 75020 Extension 75050 Extension 5509.35 Zoom Gear Optional accessories: 47140 Trim Weight	AF only. Product(s) required: 75340 Dome Port 75050 Extension 5509.35 Zoom Gear Optional accessories: 47140 Trim Weight	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
24-70 mm Sony FE f/2.8 GM	AF only. <u>Product(s) required:</u> +4 Diopter Required 75340 Dome Port 75028 Extension 75050 Extension 5509.34 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight		
24-70 mm Sony FE f/2.8 GM II	AF only. <u>Product(s) required:</u> 75340 Dome Port 75028 Extension 75042 Extension 5509.44 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight	AF only. <u>Product(s) required:</u> 75340 Dome Port 75020 Extension 75050 Extension 5509.44 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight	
24-70 mm Sony FE f/4 ZA OSS Carl Zeiss Vario Tessar T*	AF only. <u>Product(s) required:</u> +4 Diopter Required 75340 Dome Port 75028 Extension 5509.28 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight		
24-105 mm Sony FE f/4 G OSS	AF only. <u>Product(s) required:</u> +4 Diopter Required 75340 Dome Port 75020 Extension 75050 Extension 5509.16 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight		
24-240 mm Sony FE f/3.5-6.3 OSS	Lens not recommended due to zoom range.		

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
25 mm Zeiss Batis f/2	AF only. Product(s) required: 75340 Dome Port		
28 mm Sony FE f/2	Superior edge sharpness compared to shorter ports. Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75028 Extension Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port 75042 Extension	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port Optional accessories: 47140 Trim Weight
28 mm Sony FE f/2 + 16mm Fisheye Conversion Lens SEL057FEC	AF only. Product(s) required: 75340 Dome Port 75028 Extension Optional accessories: 47140 Trim Weight		
28 mm Sony FE f/2 + Ultra Wide Converter SEL075UWC	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75028 Extension Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Compact Dome Port 75042 Extension	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
28-60 mm Sony FE f/4-5.6	Superior edge sharpness compared to shorter ports. Compact and lightweight for travel. Better for close focus wide angle. Diopter required for focusing behind a dome underwater, but prevents focusing at infinity above the surface. AF only. Product(s) required: +4 Diopter Required 75344 Compact Dome Port 75050 Extension 5509.61 Zoom Gear 0923.77 Anti-Reflection Ring	Compact and lightweight for travel. Better for close focus wide angle. Diopter required for focusing behind a dome underwater, but prevents focusing at infinity above the surface. AF only. Product(s) required: +4 Diopter Required 75344 Compact Dome Port 5509.61 Zoom Gear 0923.77 Anti-Reflection Ring	Larger dome is best for split shots (half-in, half-out of the water). Diopter required for focusing behind a dome underwater, but prevents focusing at infinity above the surface. AF only. Product(s) required: +4 Diopter Required 75340 Dome Port 5509.61 Zoom Gear 0923.77 Anti-Reflection Ring Optional accessories: 47140 Trim Weight
28-70 mm Sony FE f/3.5-5.6 OSS	Superior edge sharpness compared to shorter ports. Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: +4 Diopter Required 75340 Dome Port 75042 Extension 5509.28 Zoom Gear Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: +4 Diopter Required 75344 Compact Dome Port 75050 Extension 5509.28 Zoom Gear	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: +4 Diopter Required 75340 Dome Port 5509.28 Zoom Gear Optional accessories: 47140 Trim Weight
28-75 mm Tamron f/2.8 Di III VXD G2	AF only. Product(s) required: 75340 Dome Port 75042 Extension 5509.71 Zoom Gear 5509.1 Rubber Set Optional accessories: 47140 Trim Weight		
28-135 mm Sony FE PZ f/4 G OSS	Lens not supported due to size.		
30 mm Sony E f/3.5 Macro	AF only. Product(s) required: 75301 Flat Port		

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
35 mm Sony FE f/1.4 GM	Compact and lightweight with better handling. Full angle of coverage underwater. AF only. Product(s) required: 75344 Compact Dome Port 75028 Extension	Full angle of coverage underwater. AF only. Product(s) required: 75340 Dome Port 75020 Extension Optional accessories: 47140 Trim Weight	
35 mm Sony FE f/1.4 ZA Distagon T*	Large dome is better for split shots (half-in, half-out of the water). Full angle of coverage underwater. AF only. Product(s) required: 75340 Dome Port 75042 Extension Optional accessories: 47140 Trim Weight	Reduced angle of coverage underwater. AF only. Product(s) required: 75301 Flat Port 75042 Extension	
35 mm Sony E f/1.8 OSS 35 mm Sony FE f/1.8 35 mm Sony FE f/2.8 ZA Carl Zeiss Sonnar T*	Compact and lightweight with better handling. Full angle of coverage underwater. AF only. Product(s) required: 75344 Compact Dome Port	Full angle of coverage underwater. AF only. Product(s) required: 75340 Dome Port Optional accessories: 47140 Trim Weight	Reduced angle of coverage underwater. AF only. Product(s) required: 75301 Flat Port
50 mm Sony FE f/1.2 GM	Reduced angle of coverage underwater. AF only. Product(s) required: 75301 Flat Port 75037 Extension	Compact and lightweight for travel. Full angle of coverage underwater. Diopter required when shooting underwater. AF only. Product(s) required: +4 Diopter Required 75340 Dome Port 75042 Extension Optional accessories: 47140 Trim Weight	Full angle of coverage underwater. Diopter required when shooting underwater. AF only. Product(s) required: +4 Diopter Required 75340 Dome Port Optional accessories: 47140 Trim Weight

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
50 mm Sony f/1.8 FE	AF or MF. <u>Product(s) required:</u> 75301 Flat Port 75020 Extension <u>Optional accessories:</u> 5509.27 Focus Gear		
50 mm Sony E f/1.8 OSS	AF or MF. <u>Product(s) required:</u> 75301 Flat Port <u>Optional accessories:</u> 5509.27 Focus Gear		
50 mm Sony f/2.8 Macro	AF or MF. <u>Product(s) required:</u> 75301 Flat Port 75020 Extension <u>Optional accessories:</u> 5509.28 Focus Gear	Full angle of coverage underwater. AF or MF. <u>Product(s) required:</u> 75344 Compact Dome Port 75028 Extension <u>Optional accessories:</u> 5509.28 Focus Gear	AF or MF. <u>Product(s) required:</u> 75303 Flat Port 75037 Extension <u>Optional accessories:</u> 5509.28 Focus Gear
55 mm Sony FE f/1.8 ZA Carl Zeiss Sonnar T*	AF only. <u>Product(s) required:</u> 75301 Flat Port		
55-210 mm Sony E f/4.5-6.3 OSS 70-200 mm Sony FE f/4 G OSS	Lens not recommended due to zoom range and minimum focus distance 1m (39.37").		
85 mm Sony FE f/1.4 GM	Suitable for use above the surface of the water. Lens not recommended for use underwater. AF only. <u>Product(s) required:</u> 75301 Flat Port 75042 Extension		

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
85 mm Sony FE f/1.8	Suitable for use above the surface of the water. Lens not recommended for use underwater. AF only. Product(s) required: 75301 Flat Port 75020 Extension		
90 mm Sony FE f/2.8 Macro G OSS “BEST LENS” See Installation See Review	This shorter combination is needed when using macro wet lenses attached to the front of the port. Manual focus with optional gear. Product(s) required: 75301 Flat Port 75020 Extension 75042 Extension Optional accessories: 5509.47 Focus Gear	Manual focus with optional gear. Product(s) required: 75301 Flat Port 75028 Extension 75050 Extension Optional accessories: 5509.47 Focus Gear	
90 mm Tamron f/2.8 Di III VXD	AF only. Product(s) required: 75301 Flat Port 75050 Extension	AF only. Product(s) required: 75303 Flat Port 75020 Extension 75037 Extension	
100 mm Sony FE f/2.8 Macro GM “BEST LENS”	Focus ring locks prevents accidentally changing from AF to MF during installation. Manual focus with optional gear. Product(s) required: 75301 Flat Port 75028 Extension 75042 Extension 5509.75 Focus Ring Lock Optional accessories: 5509.74 Focus Gear	Focus ring locks prevents accidentally changing from AF to MF during installation. Manual focus with optional gear. Product(s) required: 75301 Flat Port 75020 Extension 75050 Extension 5509.75 Focus Ring Lock Optional accessories: 5509.74 Focus Gear	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
100 mm Canon f/2.8 EF USM Macro (non-IS) + Metabones Canon EF Lens to Sony E Mount T Smart Adapter (Mark IV) or Sigma MC-11 Adapter <i>Tripod foot must be removed from adapter.</i>	AF only. Product(s) required: 75301 Flat Front 75020 Extension 75050 Extension		
100 mm Canon f/2.8L EF IS USM Macro + Metabones Canon EF Lens to Sony E Mount T Smart Adapter (Mark IV) or Sigma MC-11 Adapter <i>Tripod foot must be removed from adapter.</i>	AF only. Product(s) required: 75301 Flat Front 75020 Extension 75050 Extension		
105 mm Sigma f/2.8 DG DN Macro Art	AF only. Product(s) required: 75301 Flat Port 75020 Extension 75037 Extension		
135 mm Sony FE f/1.8 GM	This lens is too large to be used in the DL port system.		